



# PROTREAT BFW32F

## Corrosion Inhibitor

### FEATURES

- One-shot treatment
- Cost effective
- Easy to control
- pH adjustment functionality

### AREAS OF USE

- Boiler water treatment

### DESCRIPTION

PROTREAT BFW32F is a polymer-based boiler treatment solution. It is a blend of deposit and corrosion inhibitors for generating systems. It may also be used as an alkalinity builder in boiler systems to ensure optimum water conditioning.

### DIRECTIONS FOR USE

PROTREAT BFW32F can be used neat or as a dilute solution into the boiler feedwater. It is easily controlled with a simple test. The dosage rates depend upon the boiler feedwater quality and operating condition.

Please, consult your Jasol representative for further information.

### SAFETY INFORMATION

PROTREAT BFW32F is classified as Hazardous according to the GHS.

PROTREAT BFW32F is classified as Dangerous Goods according to the ADG Code (7<sup>th</sup> Ed).

PROTREAT BFW32F is a Scheduled Poison according to the SUSMP.

Avoid contact with eyes and skin. Refer to SDS for further information.

#### FIRST AID INFORMATION

If poisoning occurs contact a doctor or **Poisons Information Centre Australia, Phone 13 11 26**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water and seek immediate medical attention. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. If on skin, remove contaminated clothing and wash affected area with running water. Seek immediate medical attention.

**24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953**

### PRODUCT ENQUIRIES

Customer Service: **1800 334 679**

[jasolcsteam@gwf.com.au](mailto:jasolcsteam@gwf.com.au)

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

### PHYSICAL & CHEMICAL PROPERTIES

<b>FORM</b>	Liquid
<b>COLOUR</b>	Dark Brown
<b>ODOUR</b>	Odourless
<b>pH</b>	13.0-14.0
<b>SPECIFIC GRAVITY</b>	1.13 at 20°C
<b>FLAMMABILITY</b>	Not Flammable



2142100