



# PROTREAT OS155

## Corrosion Inhibitor

### FEATURES

- Biodegradable
- Natural corrosion inhibition power of tannins
- Cost effective
- For low-medium pressure boilers
- Non-hazardous
- HALAL approved

### AREAS OF USE

- Boiler water treatment

### DESCRIPTION

PROTREAT OS155 is a blend of natural and synthetic organic materials which prevents corrosion in steam generating systems by absorbing oxygen from feedwater and boiler water and by forming a protective iron tannate layer on the boiler surfaces. PROTREAT OS155 is effective at low feedwater temperatures where the use of sulphite-based oxygen scavengers becomes impractical and uneconomical.

PROTREAT OS155 also protects the boiler against scale by inhibiting the formation of calcium carbonate crystals. It is suitable for low-medium pressure boilers.

### DIRECTIONS FOR USE

PROTREAT OS155 should be dosed continuously, as a dilute solution or neat, into the boiler feedwater. Dosage should be controlled to give a boiler water tannin reserve of 100-200ppm. PROTREAT OS155 is compatible with all Jasol boiler treatment chemicals.

For assessment before use, please consult your Jasol representative.

### SAFETY INFORMATION

PROTREAT OS155 is NOT classified as Hazardous according to the GHS.

PROTREAT OS155 is NOT classified as Dangerous Goods according to the ADG Code (7<sup>th</sup> Ed).

PROTREAT OS155 is NOT a Scheduled Poison according to the SUSMP.

#### FIRST AID INFORMATION

For advice in an emergency, contact **Poisons Information Centre Australia (phone 13 11 26) or a doctor at once**. If swallowed do NOT induce vomiting. Wash out mouth thoroughly with water. If in eyes, hold eyelids apart and flood with water for at least 15 minutes. Seek medical attention if irritation persists.

**24 HOUR TOLL FREE EMERGENCY PHONE NO: 1800 629 953**

### PRODUCT ENQUIRIES

Customer Service: **1800 334 679**

[jasolcsteam@gwf.com.au](mailto:jasolcsteam@gwf.com.au)

For further information regarding product safety and handling, refer to the Safety Data Sheet and product label.

### PHYSICAL & CHEMICAL PROPERTIES

<b>FORM</b>	Liquid
<b>COLOUR</b>	Dark Brown
<b>ODOUR</b>	Odourless
<b>pH</b>	6.5-8.0
<b>SPECIFIC GRAVITY</b>	1.06 at 20°C
<b>FLAMMABILITY</b>	Not Flammable



2142020